



i62 SIP Door Phone

Description

The i62 is a SIP door phone product that integrates access control, intercom, and security functions. It features a technologically advanced design and premium intelligent manufacturing processes, equipped with a quick-dial touch button. The i62 has a high security level, meeting IP66 and IK07 protection standards, making it suitable for outdoor environments. It supports various methods of door opening for efficient access management and comes with a 2 mega pixel camera for one-touch audio and video calls. The i62 supports the SIP and ONVIF protocols, allows for integration with security devices, and is compatible with major mainstream platforms. It can be customized for various scenario solutions, making it suitable for high-end apartment buildings, office buildings, communities, and industrial parks.

Main Features



One call button for quick contact with the management office.



Equipped with a 2 mega pixel HDR high-definition camera, it provides clearer imaging.



IP66 & IK07 high protection rating, wide temperature operation, suitable for harsh outdoor environments.



Equipped with a wide range of interfaces for connecting various security devices.



Supports the standard ONVIF protocol, providing high flexibility and excellent compatibility.



APP

Outdoor

Fanvil Technology Co., LTD

Add: 10F, Block A, Dualshine Global Science Innovation Center, Honglang North 2nd Road, Bao'An District, Shenzhen, China

Phone: 0755-26402199 E-mail: sales@fanvil.com Web: www.fanvil.com

Specifications

Panel Type	Multi-apartment, Community, Hotel, Villa
Screen/Keyboard	Quick call button ×1
Body	Aluminum
Colors	Gunmetal
Sensor	1/2.9-inch, CMOS
Camera	2 Mpx, Support infrared
Viewing Angle	120°(Horizontal) 60°(Vertical)
Output Video	H.264 (Baseline, Main Profile)
Light Sensitivity	0.1Lux
Card Storage	10,000
Power Consumption	PoE: 1.69~6.84W Adapter: 1.42~5.93W
Power Supply	DC 12V / 1A POE 802.3af Class 3
Working Temperature	-40°C~+70°C
Storage Temperature	-40°C~+70°C
Size of the Panel (LWH)	177.4x88x36.15mm
IP / IK Level	IP66 / IK07
Installation	Wall-mounted Flush-mounted(Need to purchase accessories separately: EX102)

Functional Capabilities

Supported Protocols	SIP 2.0 over UDP/TCP/TLS
Lock Opening	IC/ID Card, By DTMF Code, Remote door opening
Interface	Wiegand Input/Output Short Circuit Input/Output RS485 (Reserve) Line out for induction loop
Supported Wiegand	26, 34 bit
Supported ONVIF Types	Profile S
Supported Standards	Mifare Classic 1K/4K, Mifare DESFire, Mifare Ultralight, Mifare Plus Cards 13.56 MHz, Cards 125 kHz
Talking Mode	Full duplex (High-definition Audio)
Additionally	Built-in relay, Open API, Motion detection, Tamper alarm, TF Card