



# i64 SIP Door Phone

## Description

The i64 is a SIP door phone that integrates access control, intercom, and security functions into one product. It meets the high protection standards of IP66 and IK07, ensuring a high level of security suitable for outdoor environments. The i64 supports various door opening methods for streamlined access management and is equipped with a 2 mega-pixel camera for one-touch audio and video communication. Compatible with SIP and ONVIF protocols, it integrates seamlessly with security systems and works well with major mainstream platforms. The i64 can be customized for various scenario solutions, making it suitable for upscale residential areas, office buildings, communities, and industrial parks.

## Main Features



Brand new digital keypad design with color backlight for an enhanced user experience.



Equipped with a 2 mega-pixel HDR high-definition camera, it provides clearer imaging.



IP66 & IK07 high protection rating, wide temperature operation, suitable for harsh outdoor environments.




Equipped with a wide range of interfaces for connecting various security devices.



Supports the standard ONVIF protocol, providing high flexibility and excellent compatibility.



## Community



## Specifications

<b>Panel Type</b>	Multi-apartment, Community, Hotel
<b>Screen/Keyboard</b>	12 Numeric keys+4 Function keys, Color backlight
<b>Body</b>	Aluminum
<b>Colors</b>	Gunmetal
<b>Sensor</b>	1/2.9-inch, CMOS
<b>Camera</b>	2 Mpx,Support infrared
<b>Viewing Angle</b>	120°(Horizontal) 60°(Vertical)
<b>Output video</b>	H.264 (Baseline,Main Profile)
<b>Light Sensitivity</b>	0.1Lux
<b>Card Storage</b>	1,0000
<b>Power Consumption</b>	PoE: 1.71~6.96W Adapter: 1.52~6.26W
<b>Power Supply</b>	DC 12V / 1A PoE 802.3af Class 3
<b>Working Temperature</b>	-40°C~+70°C
<b>Storage temperature</b>	-40°C~+70°C
<b>Size of the Panel (LWH)</b>	177.4x88x36.15mm
<b>IP / IK Level</b>	IP66 / IK07
<b>Installation</b>	Wall-mounted Flush-mounted(Need to Purchase Accessories Separately: EX102)

## Functional Capabilities

<b>Supported Protocols</b>	SIP 2.0 over UDP/TCP/TLS
<b>Lock Opening</b>	IC/ID Card, By DTMF Code, Remote door opening
<b>Interface</b>	Wiegand Input/Output Short Circuit Input/Output RS485 (Reserve) Line out for induction loop
<b>Supported Wiegand</b>	26, 34 bit
<b>Supported ONVIF Types</b>	Profile S
<b>Supported Standards</b>	Mifare Classic 1K/4K, Mifare DESFire, Mifare Ultralight, Mifare Plus Cards 13.56 MHz, Cards 125 kHz
<b>Talking Mode</b>	Full duplex (High-definition Audio)
<b>Additionally</b>	Built-in relay, Open API, Motion detection, Tamper Alarm, TF Card